

3 4 5

/

1 x Socket R3 (LGA 2011-3; 80x80mm; 3.7mm)

- ® ® E5-1600 v4
- ® ® E5-1600 v3
- ® ® E5-2600 v4
- ® ® E5-2600 v3

Intel® C612 PCH

: 8 (4 /CPU, 8-DIMM /CPU)

: 512GB LRDIMM

: DDR4 2133 /1866/1600/1333 RDIMM*

DDR4 2133 /1866/1600/1333 LRDIMM*

: 32GB, 16GB, 8GB, 4GB RDIMM

64GB, 32GB LRDIMM

: 6

1 : PCI-E x8 (Gen2 X4 Link)

2 : PCI 32bit/33MHz

3 : PCI-E x8 (Gen3 X8 Link)

4 : PCI-E x16 (Gen3 X16 Link), 3 x8 link

5 : PCI-E x8 (Gen3 X8 Link)

6 : PCI-E x16 (Gen3 X16 Link), 5 x8 link

7 : MIO

ATX (12"x9.6", 305mm x 244mm)

()

ASWM Enterprise

SATA :

Intel® C612

10 x SATA3 6Gb/s

9 x SATA3 6Gb/s + 1 x M.2 *2
Intel® Rapid Storage Technology Enterprise(RSTe) (Windows)
(RAID 0, 1, 5, 10)
LSI® MegaRAID (Linux/Windows)
(RAID 0, 1, 10)
SAS/SATA :
ASUS PIKE II 3008 8-port SAS HBA
ASUS PIKE II 3108 8-port SAS HW RAID

2 x Intel® I210AT + 1 x

Aspeed AST2400 + 32MB VRAM

I/O

1 x TPM
1 x PSU , 24-pin ATX + 8-pin ATX 12V
1 x , Onboard socket for optional management card
1 x USB 3.0 pin , 2
1 x USB 2.0 pin , 2
6 x , 4pin
1 x SMBus
1 x
2 x LAN LED
1 x
1 x M.2 , NGFF : 2242, : 16~128GB

I/O

2 x USB 3.1 Gen 1
2 x USB 2.0
1 x VGA
2 x GbE LAN
1 x Mgmt LAN
1 x PS/2 /

ASWM Enterprise

ASMB8-iKVM for KVM-over-Internet

: 10°C ~ 35°C
: -40°C ~ 70°C
: 20% ~ 90% ()

(1-in-1)

: 1.281 KG
: 1.7 KG

(10-in-1)
: 9.79 KG
: 12 KG

Gift Box (1-in-1) with ASMB8-IKVM
1 x ASMB8-iKVM Module
3 x Support DVD
1 x IO Shield
1 x Cable Set

Gift Box (1-in-1)
2 x Support DVD
1 x IO Shield
1 x Cable Set

Bulk Pack (10-in-1) with ASMB8-IKVM
1 x ASMB8-iKVM Module
3 x Support DVD
1 x IO Shield

Bulk Pack (10-in-1)
2 x Support DVD
1 x IO Shield

CPU

*1 EEB

*2 9 x SATA3 6Gb/s + 1 x M.2 (SATA 6Gb/s)

*3 UDIMM Core i7

Revision #2

Created 13 March 2022 01:09:17 by

Updated 9 July 2022 19:37:38 by